



Knotting

- Reduces resin seepage from knots especially in softwoods
- Suitable for use on all types of wood
- Ideal for use before painting



Product use

Liberon Knotting helps to prevent seepage from knots in resinous woods prior to painting and helps to minimise the discolouration of paint finishes. Liberon Knotting is pale in colour and may be used with clear varnish finishes.

Preparation

Ensure the surface is bare, remove any wax finishes with Liberon Wax and Polish Remover and any varnish/paint finishes with Liberon Fine Wood Stripper. If the wood is to be dyed or stained, this must be completed prior to the application of Liberon Knotting.

Application

Ensure the surface is clean, dry and free from dust. Apply one coat only of Liberon Knotting directly onto the knots.

Touch dry in 15 minutes but leave to dry a further 2 hours before applying any finishes.

Important

Liberon Knotting is not recommended for oiled or waxed surfaces. Always test product first on a spare surface or inconspicuous area to check colour, compatibility and end results. Clean brushes in methylated spirit.

Health and Safety

Highly flammable. Keep out of the reach of children. Keep away from sources of ignition – No Smoking. Do not empty into drains. Take precautionary measures against static discharges. Use only in well-ventilated areas.

Packaging

Liberon Knotting is available in 125 ml and 250 ml containers.