



TECHNICAL DATA SHEET

During Business Hours: (800) 966-3458

Outside Business Hours: (800) 420-7186

Gorilla Sealant

Product Description: Gorilla 100% Silicone Sealant is great for kitchen, bath, window, doors, plumbing, gutters and more. This clear sealant formula won't yellow, shrink or crack over time and is mold and mildew resistant. It withstands indoor and outdoor environments and is ready for water exposure in as little as 30 minutes. The removable nozzle provides excellent reusability.

Standard Size 2.8 fl. oz. (83 mL) tube

Properties (Typical)

Specifications	Meets ASTM C920 Specification for class 50 uses G,A
Chemistry	Acid cure silicone
Hardness, Durometer (Shore A)	25
Extrusion Rate	250 to 500 g/min (90 psi, 1/8" nozzle opening)
Skin-Over-Time	10 to 25 minutes, depending on conditions
Tensile Strength ASTM D412	>170 psi
Elongation ASTM D412	>350 %
Specific Gravity, 20°C	1.02
Application temperature	40 to 100°F (4 to 38°C), best >40°F
Service temperature	-40 to 350°F (-40 to 176°C)
VOC Content	< 3%
Coverage	15 lin. Ft. using 3/16" bead

Note: The technical information and data found in this data sheet is intended as representative or typical only and should not be used for specification purposes. The information is given in good faith, with tests conducted by Quality Assurance and Technical Service Departments. Bond strength and cure times are dependent on a number of factors including moisture content during cure, cure conditions, bonding material and test method. Users should determine the suitability of the product for their own purposes by their own tests.